

# SAFETY DATA SHEET

Date Printed: 05/13/2024

Date Revised: 01/15/2022

## SECTION 1. IDENTIFICATION

**Product Identifier:** (3N) 99.9% Arsenic Ethoxide

**Product Code:** AS-ETOX-03

**CAS Number:** 3141-12-6

**Relevant identified uses of the substance:** Scientific research and development

Supplier details:

American Elements  
10884 Weyburn Ave.  
Los Angeles, CA 90024  
Tel: +1 310-208-0551  
Fax: +1 310-208-0351  
Emergency telephone number:  
+1 800-424-9300

## SECTION 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture in accordance with 29 CFR 1910 (OSHA HCS)

GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.

GHS06 Skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.

Acute Tox. 3 H331 Toxic if inhaled.

Hazards not otherwise classified No data available

GHS label elements, including precautionary statements



Hazard pictograms

GHS02 GHS06

Signal word Danger

Hazard statements

H226 Flammable liquid and vapor.

H301+H331 Toxic if swallowed or if inhaled.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor  
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.  
WHMIS classification  
B3 - Combustible liquid  
D1A - Very toxic material causing immediate and serious toxic effects  
Classification system  
HMIS ratings (scale 0-4)  
(Hazardous Materials Identification System)  
HEALTH  
FIRE  
REACTIVITY  
3  
3  
2  
Health (acute effects) = 3  
Flammability = 3  
Physical Hazard = 2  
Other hazards  
Results of PBT and vPvB assessment  
PBT: N/A  
vPvB: N/A

---

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substances  
CAS No. / Substance Name:  
3141-12-6 Arsenic(III) ethoxide  
Identification number(s):  
Index number: 033-002-00-5

---

### **SECTION 4. FIRST AID MEASURES**

Description of first aid measures  
General information  
Immediately remove any clothing soiled by the product.  
Remove breathing apparatus only after contaminated clothing has been completely removed.  
In case of irregular breathing or respiratory arrest provide artificial respiration.  
If inhaled:  
Supply patient with fresh air. If not breathing, provide artificial respiration. Keep patient warm.  
Seek immediate medical advice.  
In case of skin contact:  
Immediately wash with soap and water; rinse thoroughly.  
Seek immediate medical advice.  
In case of eye contact:  
Rinse opened eye for several minutes under running water. Consult a physician.  
If swallowed:  
Do not induce vomiting; immediately call for medical help.

Information for doctor

Most important symptoms and effects, both acute and delayed:

No data available

Indication of any immediate medical attention and special treatment needed:

No data available

---

## **SECTION 5. FIREFIGHTING MEASURES**

Extinguishing media

Suitable extinguishing agents CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

Special hazards arising from the substance or mixture

Contact with water releases a flammable alcohol.

If this product is involved in a fire, the following can be released:

Toxic metal oxide fume

Carbon monoxide and carbon dioxide

Advice for firefighters

Protective equipment:

Wear self-contained respirator.

Wear fully protective impervious suit.

---

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

Environmental precautions: Do not allow material to be released to the environment without official permits.

Methods and materials for containment and cleanup:

Keep away from ignition sources.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

Prevention of secondary hazards: Keep away from ignition sources.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

---

## **SECTION 7. HANDLING AND STORAGE**

Handling

Precautions for safe handling

Handle under dry protective gas.

Keep container tightly sealed.

Store in cool, dry place in tightly closed containers.

Ensure good ventilation at the workplace.

Open and handle container with care.

Information about protection against explosions and fires:

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.  
Keep ignition sources away.  
Conditions for safe storage, including any incompatibilities  
Requirements to be met by storerooms and receptacles: No special requirements.  
Information about storage in one common storage facility:  
Store away from oxidizing agents.  
Store away from water/moisture.  
Further information about storage conditions:  
Store under dry inert gas.  
This product is moisture sensitive.  
Keep container tightly sealed.  
Store in cool, dry conditions in well-sealed containers.  
Protect from humidity and water.  
Specific end use(s) No data available

---

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Additional information about design of technical systems:  
Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.  
Components with limit values that require monitoring at the workplace:  
Arsenic, organic compounds (as As)  
mg/m<sup>3</sup>  
USA PEL 0.5  
Control parameters  
Components with limit values that require monitoring at the workplace:  
None.  
Additional information: No data  
Exposure controls  
Personal protective equipment  
Follow typical protective and hygienic practices for handling chemicals.  
Keep away from foodstuffs, beverages and feed.  
Remove all soiled and contaminated clothing immediately.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Maintain an ergonomically appropriate working environment.  
Breathing equipment: Use self-contained respiratory protective device in emergency situations.  
Protection of hands:  
Impervious gloves  
Inspect gloves prior to use.  
The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.  
Penetration time of glove material (in minutes) No data available  
Eye protection: Safety glasses  
Body protection: Protective work clothing.

---

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Information on basic physical and chemical properties  
Appearance:  
Form: Liquid

Color: Colorless  
Odor: No data available  
Odor threshold: No data available.  
pH: No data available.  
Melting point/Melting range: No data available  
Boiling point/Boiling range: 166 °C (331 °F)  
Sublimation temperature / start: No data available  
Flash point: 49 °C (120 °F)  
Flammability (solid, gas) No data available.  
Ignition temperature: No data available  
Decomposition temperature: No data available  
Autoignition: No data available.  
Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures is possible.  
Explosion limits:  
Lower: No data available  
Upper: No data available  
Vapor pressure: No data available  
Density at 20 °C (68 °F): 1.21 g/cm<sup>3</sup> (10.097 lbs/gal)  
Relative density No data available.  
Vapor density No data available.  
Evaporation rate No data available.  
Solubility in / Miscibility with  
Water: Reacts  
Contact with water releases a flammable alcohol.  
Partition coefficient (n-octanol/water): No data available.  
Viscosity:  
Dynamic: No data available.  
Kinematic: No data available.  
Other information No data available

---

## SECTION 10. STABILITY AND REACTIVITY

Reactivity No data available  
Chemical stability Stable under recommended storage conditions.  
Thermal decomposition / conditions to be avoided: Decomposition will not occur if used and stored according to specifications.  
Possibility of hazardous reactions No dangerous reactions known  
Conditions to avoid No data available  
Incompatible materials:  
Oxidizing agents  
Water/moisture  
Hazardous decomposition products:  
Toxic metal oxide fume  
Carbon monoxide and carbon dioxide

---

## SECTION 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects  
Acute toxicity:  
Toxic if inhaled.

Toxic if swallowed.

LD/LC50 values that are relevant for classification: No data

Skin irritation or corrosion: May cause irritation

Eye irritation or corrosion: May cause irritation

Sensitization: No sensitizing effects known.

Germ cell mutagenicity: No effects known.

Carcinogenicity:

EPA-A: human carcinogen: sufficient evidence from epidemiologic studies to support a causal association between exposure and cancer.

IARC-1: Carcinogenic to humans: sufficient evidence of carcinogenicity.

ACGIH A1: Confirmed human carcinogen: Agent is carcinogenic to humans based on epidemiologic studies of, or convincing clinical evidence in, exposed humans.

Carcinogen as defined by OSHA.

NTP-K: Known to be carcinogenic: sufficient evidence from human studies.

Reproductive toxicity: No effects known.

Specific target organ system toxicity - repeated exposure: No effects known.

Specific target organ system toxicity - single exposure: No effects known.

Aspiration hazard: No effects known.

Subacute to chronic toxicity:

Acute arsenic poisoning from ingestion results in marked irritation of the stomach and intestines with nausea, vomiting and diarrhea. In severe cases, the vomitus and stools are bloody and the patient goes into collapse and shock with weak, rapid pulse, cold sweats, coma and death.

Chronic arsenic poisoning may cause disturbances of the digestive system such as loss of appetite, cramps, nausea, constipation or diarrhea.

Subacute to chronic toxicity: No effects known.

Subacute to chronic toxicity:

Ethyl alcohol, if formed, is a central nervous system depressant. Ingestion leads to drowsiness, lassitude, loss of appetite and inability to concentrate.

Additional toxicological information: To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

---

## SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity: No data available

Persistence and degradability No data available

Bioaccumulative potential No data available

Mobility in soil No data available

Ecotoxicological effects:

Remark: Very toxic for aquatic organisms

Additional ecological information:

Do not allow material to be released to the environment without official permits.

Do not allow product to reach groundwater, water courses, or sewage systems, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

May cause long lasting harmful effects to aquatic life.

Avoid transfer into the environment.

Very toxic for aquatic organisms

Results of PBT and vPvB assessment

PBT: N/A

vPvB: N/A

Other adverse effects No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Recommendation Consult official regulations to ensure proper disposal.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

---

## SECTION 14. TRANSPORT INFORMATION

UN-Number

DOT, IMDG, IATA UN2929

UN proper shipping name

DOT Toxic liquids, flammable, organic, n.o.s. (Arsenic(III) ethoxide)

IMDG TOXIC LIQUID, FLAMMABLE, ORGANIC, N.O.S. (Arsenic(III) ethoxide), MARINE POLLUTANT

IATA TOXIC LIQUID, FLAMMABLE, ORGANIC, N.O.S. (Arsenic(III) ethoxide)

Transport hazard class(es)

DOT

Class 6.1 Toxic substances.

Label 6.1+3

Class 6.1 (TF1) Toxic substances

Label 6.1+3

IMDG

Class 6.1 Toxic substances.

Label 6.1+3

IATA

Class 6.1 Toxic substances.

Label 6.1+3

Packing group

DOT, IMDG, IATA II

Environmental hazards: Environmentally hazardous substance, liquid; Marine Pollutant

Marine pollutant (IMDG): Symbol (fish and tree)

Special precautions for user Warning: Toxic substances

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code N/A

Transport/Additional information:

DOT

Marine Pollutant (DOT): No

Remarks: Special marking with the symbol (fish and tree).

UN "Model Regulation": UN2929, Toxic liquids, flammable, organic, n.o.s. (Arsenic(III) ethoxide), 6.1 (3), II

---

## SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

GHS label elements, including precautionary statements

Hazard pictograms

GHS02 GHS06

Signal word Danger

#### Hazard statements

H226 Flammable liquid and vapor.

H301+H331 Toxic if swallowed or if inhaled.

#### Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### National regulations

This product is not listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical Substance Inventory. Use of this product is restricted to research and development only. This product must be used by or directly under the supervision of a technically qualified individual as defined by TSCA. This product must not be used for commercial purposes or in formulations for commercial purposes.

SARA Section 313 (specific toxic chemical listings)

3141-12-6 Arsenic(III) ethoxide

#### California Proposition 65

Prop 65 - Chemicals known to cause cancer Substance is not listed.

Prop 65 - Developmental toxicity Substance is not listed.

Prop 65 - Developmental toxicity, female Substance is not listed.

Prop 65 - Developmental toxicity, male Substance is not listed.

#### Information about limitation of use:

For use only by technically qualified individuals.

This product contains arsenic and is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and 40CFR372.

This product is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and 40CFR372.

#### Other regulations, limitations and prohibitive regulations

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006. Substance is not listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.

Substance is not listed.

Annex XIV of the REACH Regulations (requiring Authorisation for use) Substance is not listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

---

## 16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022 AMERICAN ELEMENTS. LICENSED GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.

**AMERICAN ELEMENTS** | 10884 WEYBURN AVE. | LOS ANGELES, CALIFORNIA 90024  
TEL. 310-208-0551 | FAX 310-208-0351 | customerservice@americanelements.com